

Granville Hypalube C3 FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

PRODUCT DESCRIPTION

Granville Hypalube C3 fully synthetic engine oil has been specially formulated to meet the requirements of a Low SAPS (Sulphated Ash, Phosphorus and Sulphur) engine oil. Hypalube C3 is suitable for use in vehicles fitted with exhaust after treatment devices that recommend a lubricant of the grade and specification

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C3
API: SN/CF
BMW: LL-04
GM: Dexos™ 2
MB: 229.31, 229.51 & 229.52
VW: 505.00 & 505.01
Opel: OV0401547-D30

PRODUCT BENEFITS

- * Fully Synthetic Formulation
- * Long Life capabilities
- * Protects engine at optimum temperature and performance
- * For use with exhaust after treatment devices

PRODUCT USAGE

Use as per the engine manufacturers recommendations

DIRECTIONS FOR USE

Use as per the engine manufacturers recommendations



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	0526	5020618005261
5 Litre	0527	5020618005278
20 Litre	0564	5020618005643
199 Litre	0529	5020618005292



Granville Hypalube C3 FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

STORAGE INSTRUCTIONS

Store sealed in a cool, dry place

SHELF LIFE

5 years from date of manufacture.

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	<12.5	12.3
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	7		7.98
Pour Point	ASTM D97	°C		-36	
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		10	
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			73.3
Density	ASTM D792	@ 15°C			0.85

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

